



## G-800-E

Network Switch

سوئیچ ۸ پورت غیر مدیریتی G-800-E دارای ۸ پورت گیگ. جذابیت اصلی این سوئیچ در استفاده از متریال پلاستیک در بدنه آن می باشد. این سوئیچ با امکان بهبود سرعت ارسال فایل های بزرگ، مشکل فریز شدن فیلم و یا از دست رفتن تصاویر را برطرف نموده است و گزینه ای مناسب برای هتل ها، بانک ها، دانشکده ها، و بخش هایی از کارخانه ها و شرکت های کوچک و متوسط خواهد بود.

### ویژگی های اصلی

- دارای بدنه پلاستیکی
- تعداد پورت : ۸ پورت گیگ
- پشتیبانی از full-duplex based on IEEE802.3x and half-duplex based on backpressure
- سرعت پورت ها : RJ45 10/100/1000
- پشتیبانی از non-blocking wire-speed forwarding
- مصرف برق پایین و بدون فن

### KEY FEATURES PoE SWITCH

- Fixed Port: 8\*10/100/1000Base-T RJ45 ports
- Ethernet Port: 10/100/1000Base-T auto-sensing, full/half duplex MDI/MDI-X self-adaption.
- Twisted Pair transmission: 10BASE-T: Cat3,4,5 UTP(≤100 meter)  
100BASE-TX: Cat5 or later UTP(≤100 meter)  
1000BASE-T: Cat5e or later UTP(≤100 meter)
- Network Protocol: IEEE802.3 10BASE-T, IEEE802.3i 10Base-T  
IEEE802.3u 100Base-TX, IEEE802.3ab 1000Base-T, IEEE802.3x
- Forwarding Mode: Store and Forward(Full Wire Speed)
- Switching Capacity: 16Gbps (Non-blocking)

### APPLICATION

- ▶ WIRELESS ACCESS POINT
- ▶ IP CAMERA
- ▶ IP PHONE
- ▶ COMPUTER NETWORKS

## FEATURES

Fixed Port	8*10/100/1000Base-T RJ45 ports (Data)
Model	G-800-E
Twisted Pair Transmission	10BASE-T: Cat3,4,5 UTP(≤100 meter) 100BASE-TX: Cat5 or later UTP(≤100 meter) 1000BASE-T: Cat5e or later UTP(≤100 meter)
Network Protocol	IEEE802.3 10BASE-T, IEEE802.3i 10Base-T IEEE802.3u 100Base-TX, IEEE802.3ab 1000Base-T, IEEE802.3x
Forwarding Mode	Store and Forward(Full Wire Speed)
Switching Capacity	16Gbps (Non-blocking)
Forwarding Rate/64byte	11.9Mpps
PoE Type	End-span
Buffer Memory	2M
LED Indicator	Power: PWR (green), Network:Link/Act(green)
Total PWR / Input Voltage	5W/ (DC5V)
Power Supply	External power adapter, AC100~240V 50-60Hz 0.56A
Operation TEMP / Humidity	0~+55°C, 5%~90% RH Non condensing
Storage TEMP / Humidity	-40~+75°C, 5%~95% RH Non condensing
Dimension (L*W*H)	140*78*32mm
Net /Gross Weight	<0.15kg /<0.3kg
Installation	Desktop, wall mounted

## DIMENSIONS

